

### Titan AS / NZ

# **Specification**

- Double Pole isolation
- Twin fuse, 25A maximum rating
- Designed and tested in accordance with BS7654
- AS/NZS 3000 removable MEN link in dedicated terminals
- Terminals for loop-in, loop-out supply cable
- Terminal blocks accept up to 25mm<sup>2</sup> conductors
- Accepts fuse links to BS88 Part 1, AC tag type
- IP22 rating

#### **Features**

- Cam operated lever for easy and safe fuse disconnection
- PA glass filled thermoplastic fuse carrier and base with interlocking covers
- Electro-tin plated terminal blocks and
- bored to aid cable retention with 3mm pinching screws
- Terminal blocks and contact clips retained by Torx security screws
- Fully shielded test probe access
- Clearly legible embossed terminal markings
- Insulated gland plate with cable entry via two 25mm diameter PVC conical grommets

- Angle upper cable exit assists drip arrest
- Pre-loaded PX2 Pozidrive corrosion resistant fixing screws to attach to backboard
- Captive cover screws suitable for Pozidrive or slotted fixing
- Terminal blocks equipped with serrated Separate DNO and Local Authority seal provision
  - Fully recycable plastic and metallic parts







### Titan AS / NZ

#### Construction


- Body and fuse carrier PA6
- Red incoming cable cover ABS
- Incoming/outgoing terminals electro-tin plated brass
- Contact clips electro-tin plated phosphor bronze
- Incoming cable grommets soft PVC
- Terminal screws brass 3mm slotted
- Backboard fixing screws bright zinc passivated steel


#### **Performance**


- Rated operational voltage 230VAC 50/60Hz
- Rated continuous current 25A
- Maximum environmental pollution Degree 3
- Environmental conditions -25 to +40 Celsius
- IP rating IP22
- Recommended terminal torque setting 2.25Nm

# **Alternative Options**

• Extension troughs to cater for longer cable sizes











Part Code	Description

THM0090577 Titan 25A (CNE) 3TTN 3TTE - 2D06 - LINK supplies with 2 x 6A fuses fitted

MI SYSTEMS

Lucy Zodion