

COMPACT DIMENSION FUSE-LINKS

TYPE CDS

230/240 & 400/415 Volt Compact Dimension Fuse-Links to IEC 60269-2/BS 88-2

Rated Voltages 240 & 415V a.c. Breaking Capacities 20kA at 240V, 80kA at 415V Breaking Range and Utilisation Category gG



Lawson type CDS Compact Dimension Fuse-Links are for use in single or three phase commercial or industrial installations and can be fitted into Clipfit Fuse-Holders (see page 15 of the short form catalogue) or suitable distribution fusegear.

The Lawson CLIPFIT range has rated voltages of 240V a.c. or 415V a.c. and has been certified at a test recovery voltage of at least 110%.



PRODUCT DETAILS

VOLTAGE, CURRENT RATINGS AND PRINCIPAL DIMENSIONS

List Reference	Current Rating (A)	BS88 Reference	Voltage Rating (V)	Breaking Capacity (kA)	Overall Length	
					mm	ins
SS2	2	E1	240V a.c.	20kA a.c.	51	2
SS4	4	E1				
SS6	6	E1				
SS10	10	E1				
SS16	16	E1				
SS20	20	E1				
SS25	25	E1				
SS32	32	E1				

List Reference	Current Rating (A)	BS88 Reference	Voltage Rating (V)	Breaking Capacity (kA)	Overall Length	
					mm	ins
NS2	2	F1	415V a.c.	80kA a.c.	62	2 ⁷ / ₁₆
NS4	4	F1				
NS6	6	F1				
NS10	10	F1				
NS16	16	F1				
NS20	20	F1				
NS25	25	F1				
NS32	32	F1				
NS20M25	20,25	F1				
NS20M32	20,32	F1				
NS20M40	32,40	F1				
NS20M50	32,50	F1				
NS20M63	32,63	F1				

List Reference	Current Rating (A)	BS88 Reference	Voltage Rating (V)	Breaking Capacity (kA)	Overall Length (L)	
					mm	ins
MES10	10	F2	415V a.c.	80kA a.c.	69	2 ¹¹ / ₁₆
MES16	16					
MES20	20					
MES25	25					
MES32	32					
MES40	40					
MES50	50					
MES63	63					